

DT01 Rec'd PCT/PTC 19 JAN 2005

CLAIM AMENDMENTS

Amended claims: 1-13

1. (Currently Amended) A process for operating a blue flame burner comprising burning a Fischer-Tropsch derived fuel to produce flue gasses. Use of a Fischer-Tropsch derived fuel in a blue flame burner.
2. (Currently Amended) The process of Use according to claim 1, wherein the further comprising operating under conditions such that lambda is between 1 and 1.6
3. (Currently Amended) The process of Use according to claim 2, wherein the lambda is between 1.05 and 1.2.
4. (Currently Amended) The process Use according to any one of claims 1-3, wherein the flue gases as obtained by said use are used to further comprising heating water with the flue gasses by means of indirect heat exchange in a boiler.
5. (Currently Amended) The process Use according to any one of claims 1-3, wherein the flue gases as obtained by said use are used to directly further comprising heating a space directly with the flue gasses.
6. (Currently Amended) The process Use according to any one of claims 1-5, wherein the Fischer-Tropsch derived fuel boils for more than 90 wt% between 160 °C and 400 °C.
7. (Currently Amended) The process of Use according to claim 6, wherein the Fischer-Tropsch derived fuel boils for more than 90 wt% between 160 °C and 370 °C.
8. (Currently Amended) The process Use according to any one of claims 1-7, wherein the Fischer-Tropsch derived fuel comprises a Fischer-Tropsch product which contains more than 80 wt% of iso and normal paraffins, less than 1 wt% aromatics, less than 5 ppm

sulphur sulfur and less than 1 ppm nitrogen and wherein the density of the Fischer-Tropsch product is between 0.65 g/cm³ and 0.8 g/cm³ at 15 °C.

9. (Currently Amended) The process of Use according to of claims 1-8, wherein the Fischer-Tropsch derived fuel comprises more than 80 wt% of a Fischer-Tropsch product.

10. (Currently Amended) The process of Use according to claim 9, wherein the Fischer-Tropsch derived fuel comprises a mineral oil fraction and/or a non-mineral oil fraction.

11. (Currently Amended) The process Use according to any one of claims 1-10, wherein the Fischer-Tropsch derived fuel comprises one or more additives.

12. (Currently Amended) The process of Use according to claim 11, wherein the Fischer-Tropsch derived fuel comprises an odor marker.

13. (Currently Amended) The process of Use according to of claims 11-12, wherein the Fischer-Tropsch derived fuel comprises a color marker.